



- ⦿ 25 kW output
- ⦿ Single gun
- ⦿ CCS-2 (Combined Charging System)
- ⦿ OLED screen
- ⦿ Power & Charging Status
- ⦿ With Internet communication & RFID card options

ChargeGrid MARK-GL06P3(25)

Technical Specifications



INPUT POWER	
Input Voltage (AC)	3 Phase, 415V
Input Frequency	50 / 60 Hz
Wires	5 wires : L1,L2,L3,N,PE
OUTPUT POWER	
Number of Outputs	1
Output Connector	CCS-2
Output Voltage	200 – 500Vdc, Max 60A
Output Rating	25 kW
ENVIRONMENT	
Ambient Temperature	-40°C to 85°C
Operating Temperature	-30°C to 50°C
Altitude	Upto 2000 Mtr.
Humidity	5 to 95%
PROTECTION	
Protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, emergency shutdown with alarm, protection against electric shock
Compliance & Safety	IEC
USER INTERFACE & CONTROL	
Display	2.7" OLED Screen
Language	English
Emergency Stop	Mushroom type push button
User Authentication	RFID
Visual Indication	Error Indication, Presence of Input Supply
COMMUNICATION	
Charger & CMS	OCPP 1.6
Network Connection	Ethernet, Sim Card (optional at additional cost)
MECHANICAL	
Charging Cable Length	4 meters
Ingress Protection	IP55
Cooling	Forced Air Cooling
Dimensions (W x H x D)	680mm x 430mm x 230mm
Charger Weight	47 Kg