



- ◎ 25kW CCS-2 + 25kW CCS-2 output
- ◎ Dual gun (CCS-2 + CCS-2)
- ◎ LCD display with touchscreen
- ◎ Power, Charging Status & Fault indicators
- ◎ With Internet communication & RFID card options

ChargeGrid MARK-GD06P3(60)

Technical Specifications



INPUT POWER	
Input Voltage (AC)	3 Phase, 415V
Input Frequency	50Hz
Wires	5 wires : L1,L2,L3,N,PE
OUTPUT POWER	
Number of Outputs	2
Output Connector	CCS-2 + CCCS-2
Output Voltage DC -Vdc	200 – 1000 Vdc
Output Rating	50kW (25 kW CCS-2 + 25 kW CCS-2)
ENVIRONMENT	
Ambient Temperature	0°C to 50°C
Operating Temperature	0°C to 60°C
Altitude	Upto 2000 Mtr.
Humidity	0 to 95%
PROTECTION	
Protection	Over voltage, under voltage, over current, short circuit, surge protection, over temperature, emergency shutdown with alarm, protection against electric shock
USER INTERFACE & CONTROL	
Display	7" TFT LCD Touch Screen
Language	English
Emergency Stop	Mushroom type push button
User Authentication	Mobile App/ RFID
Visual Indication	Error Indication, SOC, Presence of Input Supply
COMMUNICATION	
Charger & CMS	OCPP 1.6
Network Connection	Ethernet, Sim Card (optional at additional cost)
MECHANICAL	
Charging Cable Length	5 meters
Ingress Protection	IP55
Cooling	Forced Air Cooling
Dimensions (H x W x D)	1900mm x 800mm x 500mm
Weight	325 Kg